

Application Guidelines

For the application of Digital and Sign Media



Vehicle Preparation Guide – Vinyl Decal Application

Materials Required;

Bottle 1 - water mixed with a few drops of baby shampoo
Bottle 2 - TFR (Traffic Film Remover), Tar glue remover
Bottle 3 - Wax silicone remover
Bottle 4 - Isopropanol/water – mix of 50/50 or 70/30
Bottle 5 - 100% isopropanol or preferred final cleaning product
Cloth /paper towel - lint free
Towel - Micro fibre
DO NOT USE BLUE ROLL

Pre-Installation;

Vehicle delivered prior to installation to acclimatise. E.g. afternoon before install.
If a new vehicle, request PDI (Pre-Delivery Inspection) do not use wax silicones.
If customer cleans request no wax, silicones.
Steam clean panel/s, vinyl is to be applied to.

Cleaning;

Step 1 - Use Bottle 1 to remove any standing dirt and grime.
Step 2 - Older Vehicles - Use BOTTLE 2 to remove Traffic Film.
Step 3 - New Vehicles - Use BOTTLE 3 to remove Wax Silicones.
Step 4 - Use BOTTLE 4 – To Flush off Immediately 2 or 3.
Step 5 - Use BOTTLE 5 – Final Clean.

Please note:

Make sure installer does final cleaning and make sure THEY are happy.
Use a lot of pressure on cloth when doing final clean of Recesses, indents, edges etc.
Change cloth and turn regularly. Do not cross contaminate cloths.

Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147
○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk
www.metamark.co.uk